



# CAT 5e UTP PATCH CABLE

105-5000/5100/5200/5300/5500/5600

Phone +33 75 864 2169

Email info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100 Grenoble, France.



## Industry Standards

- ISO/IEC 11801:2002
- TIA-568.2-D Cat 5e
- EN 50173-1:2011 Class E
- ETL Verified AS/CA S008:2020

## Applications

- 1000BASE-TX Gigabit Ethernet
- 1000BASE-T Gigabit Ethernet
- 100BASE-TX Fast Ethernet
- 10BASE-T Ethernet
- Voice, Video, and other applications

## Overview

- Constructed from high-quality four-pair 24 AWG stranded copper wire
- Available in various colors and lengths
- Pre-terminated with RJ45 plugs
- Features anti-snap slim strain relief slip-on boots

## Ordering Information

Part No	Description	Color	Part No	Description	Color	Part No	Description	Color
105-5000_1	CAT.5E 0.5M PATCH CORD	GRAY	105-5200_1	CAT.5E 2M PATCH CORD	GRAY	105-5500_1	CAT.5E 5M PATCH CORD	GRAY
105-5000_2	CAT.5E 0.5M PATCH CORD	BLUE	105-5200_2	CAT.5E 2M PATCH CORD	BLUE	105-5500_2	CAT.5E 5M PATCH CORD	BLUE
105-5000_3	CAT.5E 0.5M PATCH CORD	GREEN	105-5200_3	CAT.5E 2M PATCH CORD	GREEN	105-5500_3	CAT.5E 5M PATCH CORD	GREEN
105-5000_4	CAT.5E 0.5M PATCH CORD	YELLOW	105-5200_4	CAT.5E 2M PATCH CORD	YELLOW	105-5500_4	CAT.5E 5M PATCH CORD	YELLOW
105-5000_5	CAT.5E 0.5M PATCH CORD	RED	105-5200_5	CAT.5E 2M PATCH CORD	RED	105-5500_5	CAT.5E 5M PATCH CORD	RED
105-5000_6	CAT.5E 0.5M PATCH CORD	BLACK	105-5200_6	CAT.5E 2M PATCH CORD	BLACK	105-5500_6	CAT.5E 5M PATCH CORD	BLACK
105-5100_1	CAT.5E 1M PATCH CORD	GRAY	105-5300_1	CAT.5E 3M PATCH CORD	GRAY	105-5600_1	CAT.5E 10M PATCH CORD	GRAY
105-5100_2	CAT.5E 1M PATCH CORD	BLUE	105-5300_2	CAT.5E 3M PATCH CORD	BLUE	105-5600_2	CAT.5E 10M PATCH CORD	BLUE
105-5100_3	CAT.5E 1M PATCH CORD	GREEN	105-5300_3	CAT.5E 3M PATCH CORD	GREEN	105-5600_3	CAT.5E 10M PATCH CORD	GREEN
105-5100_4	CAT.5E 1M PATCH CORD	YELLOW	105-5300_4	CAT.5E 3M PATCH CORD	YELLOW	105-5600_4	CAT.5E 10M PATCH CORD	YELLOW
105-5100_5	CAT.5E 1M PATCH CORD	RED	105-5300_5	CAT.5E 3M PATCH CORD	RED	105-5600_5	CAT.5E 10M PATCH CORD	RED
105-5100_6	CAT.5E 1M PATCH CORD	BLACK	105-5300_6	CAT.5E 3M PATCH CORD	BLACK	105-5600_6	CAT.5E 10M PATCH CORD	BLACK



# PRODUCT TECHNICAL SPECIFICATION | CAT 5e UTP PATCH CABLE

---

## Product Electrical Characteristics:

- Conductor size: 24 AWG stranded copper wire
- Plug minimum operating life: 750 insertion cycles
- RJ45 plug and boot material: Clear polycarbonate
- Material thickness: 0.35mm thick copper alloy
- Contact plating: Selective gold

## Sheath Physical Properties:

- Sheath material: PVC
- Nominal outer diameter (O.D.): 5.9mm
- Bend radius: 4 times the O.D.
- Operating temperature range: -20°C to +70°C

### HEADQUARTERS



A&G Technologies CO., Limited,  
Log 202, 5rue Albert Thomas, 38100  
Grenoble, France.

+33 75 864 2169

### REGIONAL OFFICE



A&G Technologies (HK) CO., Limited,  
Room 803, Chevalier House, 45-51 Chatham Road  
South, Tsim Sha Tsui, Kowloon, Hong Kong.

+852 5420 8788

### CONNECT THE FUTURE



info@angnetworks.com



www.angnetworks.com

© 2024 A&G Technologies. All Rights Reserved.