



CAT 3 TELEPHONE CABLE 25P INDOOR

114-30125

Phone
+33 75 864 2169

Email
info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100
Grenoble, France.



Overview

- Category: UTP CAT 5-25P-PVC Cable
- Suitable for indoor applications requiring CAT 3 telephone connections.

Industry Standard

- ISO/IEC 11801
- TIA-568-C.2
- YD/T1019

Applications


- Voice
- T1
- 4Mbps Token Ring (IEEE 802.5)
- 10 Base-T (IEEE 802.3)
- 52 Mbps ATM
- VG-Any LAN
- ISDN

Ordering Information

Part Number	Description
114-30125	CAT. 3 TELEPHONE CABLE 25 PAIR INDOOR 1M

General Information

- Conductor Material: Solid Bare Copper
- Conductor Nominal O.D.: 0.500 mm
- Conductor Material: HDPE
- Conductor Tolerance: UP +0.005 / DOWN -0.005
- Insulation Diameter: 0.90±0.04mm
- Insulation Color:
 1. Bl./ Wh.-Bl. Ora./Wh.-Ora. Gn./Wh.-Gn. Br./Wh.-Br. Gr./Wh.-Gr. Bl./ Re.-Bl. Ora./ Re.-Ora. Gn./ Re.-Gn. Br./ Re.-Br. Gr./ Re.-Gr. Bl./ Bla.-Bl. Ora./ Bla.-Ora. Gn./ Bla.-Gn. Br./ Bla.-Br. Gr./ Bla.-Gr. Bl./ Yel.-Bl. Ora./ Yel.-Ora. Gn./ Yel.-Gn. Br./ Yel.-Br. Gr./ Yel.-Gr. Bl./ Pur.-Bl. Ora./ Pur.-Ora. Gn./ Pur.-Gn. Br./ Pur.-Br. Gr./ Pur.-Gr.
- Sheath Thickness: 1.0±0.2 mm
- Sheath External O.D: 13.5 ±0.8 mm
- Sheath Material: PVC (complies with RoHS)
- Sheath Color: White
- Surface Print Error and Space: ≤ ±0.5%, 1m
- Surface Printing Letter Height: 3.0 ± 0.3 mm
- Rip-Cord: Yes
- Drain Wire: No



PRODUCT TECHNICAL SPECIFICATION | CAT 3 TELEPHONE CABLE 25P INDOOR

Product Electrical Characteristics:

- DC Resistance 20°C(Ω/100m)max: 9.5
- DC conductor resistance unbalance (%) max: 5.0
- Mutual Capacitance (1 kHz): 5.6nF/km
- Pair to ground capacitance unbalance Max: 330pF/100m
- Insulation resistance at 20°C Min: 5000MΩ.km
- Insulation dielectric strength DC 1000V for 1min: Pass

Sheath Physical Properties:

- Before Aging Tensile Strength: ≥13.5 Mpa
Elongation: ≥150%
- After Aging Tensile Strength: ≥12.5 Mpa
Elongation: ≥125%
- Installation Temperature: 0°C to +50°C
- Operating Temperature: -20°C to +60°C

Technical Performance

Frequency (MHz)	RL (≥dB)	Attenuation (≤dB)	NEXT (≥dB)
1.0	13	3.5	36
4.0	13	6.0	28
8.0	11	8.8	23
10.0	11	10.0	22
16.0	09	12.5	19

Frequency (MHz)	PSNEXT (db) ≥	ELFEXT (dB) ≥	PSELFEXT (dB) ≥
1	32	38	36
4	23	30	28
8	18	25	22
10	17	24	21
16	15	22	19

HEADQUARTERS



A&G Technologies CO., Limited,
Log 202, 5rue Albert Thomas, 38100
Grenoble, France.

+33 75 864 2169

REGIONAL OFFICE



A&G Technologies (HK) CO., Limited,
Room 803, Chevalier House, 45-51 Chatham Road
South, Tsim Sha Tsui, Kowloon, Hong Kong.

+852 5420 8788

CONNECT THE FUTURE



info@angnetworks.com



www.angnetworks.com

© 2024 A&G Technologies. All Rights Reserved.