



10 PAIR LSA KRONE MODULE AND PROTECTOR MAGAZINE

12X-00010

Phone
+33 75 864 2169

Email
info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100
Grenoble, France.



Overview

- Material: Body: PBT or ABS(UL94V-0)
- Connector: Phosphor Bronze, Silver Plating: 0.5 urn, 1.25 urn, 5 urn
- Can be installed on krone type stainless steel back mount frames for mounting on MDF, racks, profile bracket, indoor and outdoor distribution box, cross connection cabinets.

Applications

- Main distribution frames of exchanges.
- In cross-connection cabinets and terminating boxes.
- In building entrance distributors.
- In-floor distributors or in PABXs for voice and data distribution.

Ordering Information

Part Number	Description
124-00010	10 PAIR LSA KRONE MODULE
124-00010	PROTECTOR MAGAZINE WITH 3 POLE LIGHTING ARRESTOR

PRODUCT TECHNICAL SPECIFICATION | 10 PAIR LSA KRONE MODULE AND PROTECTOR MAGAZINE

Product Electrical Characteristics:

- Insulation resistance: 1000 months minimum
- Performance impedance: 120 ohm
- Contact resistance: 7 months maximum
- Dielectric intensity: AC 1000 Vrms 50Hz or 60Hz in 60s

Product Physical Properties:

- Insertion force: 40~75N
- Pull out force: $F \geq 25N$ (axial) $F \geq 5N$ (radial)
- IDC life: 200 times(20-28 AWG Solid Wire) minimum
- Copper Conductor Diameter: $\phi 4 \sim \phi 0.8$ (mm)
- Relative Humidity: 95% non condition
- Safety: FCC Part 15 Class A, CE Mark
- Operating Temperature: 10°C to 60°C
- Storage Temperature: 40°C to 70°C

HEADQUARTERS



A&G Technologies CO., Limited,
Log 202, 5rue Albert Thomas, 38100
Grenoble, France.

+33 75 864 2169

REGIONAL OFFICE



A&G Technologies (HK) CO., Limited,
Room 803, Chevalier House, 45-51 Chatham Road
South, Tsim Sha Tsui, Kowloon, Hong Kong.

+852 5420 8788

CONNECT THE FUTURE



info@angnetworks.com



www.angnetworks.com